HOTSPOT-Ex

Industrial infrared heat detector with programmable internal signal evaluation for the detection of hot surfaces, flames and moving ember – suitable up to ATEX zone 20.



Characteristics

- Robust design with aluminium diecast housing
- High resistance to moisture and dust (IP 65)
- Extremely fast response
- Separate alarm thresholds up to 16 zones
- Detection of embers
- Independent of building thermal conditions
- Integrated purge air adapter
- Low wiring effort due to common data and power transmission in a pre-assembled cable
- Central data acquisition and visualization via PC software
- Can be integrated into existing fire alarm systems
- Also suitable for process monitoring
- Certified for use up to ATEX zone 20

Applications

- Production sites for coal, biomass, wood, paper, plastic, substitute fuel, etc.
- Storage facilities and bunkers with self-igniting materials
- Drives, shredders, driers, chutes and hoppers
- Silos and mills
- Chemical industry

ADICOS HOTSPOT-Ex is a thermographic detectors of the Advanced Discovery System (ADICOS®), which was specifically designed to provide reliable early fire detection in harsh industrial environments. Application fields are areas endangered up to ATEX zone 20.

HOTSPOT-Ex are parametrizable compact infrared camera systems with integrated signal processing and evaluation. An additional conventional camera assists with orientation and alignment. The sturdy design protects against the penetration of dust and moisture. Typical applications are for example the detection of overheating drives or bearings of conveyor systems, the monitoring of spontaneously inflammable bulk materials on conveyor belts or in storage facilities and in mixing processes in chemical engineering.

A simple wiring concept with prewired ADICOS system cables and connection boxes keeps the installation simple and fast.

The HOTSPOT-Ex is connected via an ADICOS M-BUS-MASTER to a PC. Using the ADICOS system software, the measurement results can be displayed, analyzed and documented. The software allows individual parameterization and adaptation of the alarm thresholds to the environment of the respective detector.

HOTSPOT-Ex – Specifications

Mechanical dimensions



Connection cable Ø13 mm prewired

Mechanical characteristics	
Enclosure	*Coated aluminum diecast (corrosion-resistant)*
Weight	*2.3 kg (with 10 m connection cable)*
Degree of protection	*IP65*
Dimensions	*128 mm x 100 mm x 90 mm (Length x Width x Depth), (Length: cable gland included)*
Explosion protection	BVS 15 ATEX E102 *II 1D Ex ta IIIC T110°C Da* *II 2D EX tb IIIC T80°C Db* IECEx BVC 15.0089 *Ex ta IIIC T110°C Da* *EX tb IIIC T80°C Db* *EX tc IIIC T80°C Dc*
Device group (ATEX)	*II, category 1D/2D*

Thermal characteristics	
Relative humidity	*≤ 95 % (non-condensing)*
Temperature range	*–10 ... +50 °C*

Electrical characteristics	
Supply voltage	*DC 21.6 ... 40 V*
Power consumption	*2 VA / 10 VA (with / without heating)*
Internal fusing	*500 mA*
M-Bus max. line length	*≈ 2 km*
M-Bus max. line capacity	*≈ 200 nF*
M-Bus baudrate	*4800 baud*
Limit contact alarm relay	*40 V / 20 mA max. (Alarm NO relay)*
Limit contact error relay	*40 V / 20 mA max. (Error NC relay)*

Purge air requirements	
Air purity grade	*Dust ≥ 2 — Water ≥ 3 — Oil ≥ 2 (< 0.1 mg/m³)*
Air flow rate, settled air	*> 2 l/min*
Air flow rate, flowing air	*> 8 l/min (Testing may be necessary!)*

Detector characteristics	
Sensor resolution	*32 Pixel x 31 Pixel*
Optical angle	*60° x 58° | 93° x 92°*
Reaction time	*< 1 s*
Temporal resolution	0,1 s oder 1 s (depends on configuration)

GTE Industrieelektronik GmbH
Helmholtzstr. 21, 38-40 | 41747 Viersen, GERMANY | ☎ +49 2162 3703-0 | support.adicos@gte.de | www.adicos.com

HOTSPOT-Ex – Specifications

ADICOS topology concept



LEGEND:

Option: Fire panel interface or analog signal to FDnet or LSNi (e.g. SIEMENS, BOSCH) or pre-alarm

M-Bus: Connection of ADICOS service interface

NT / USV: External power supply / uninterruptible power supply



12-pin cable, OELFLEX 415CP

Wire	Signal	Limit value Contact
1	Operating voltage DC 21,6 ... 40 V non-polarised	
2		
3	M-Bus max. 40 V non-polarised	
4		
5	Relay output X6 e	Alarm NO[1]
6	Relay output X6 a	Alarm NO[1]
7	Relay output X7 a	Fault NC
8	Relay output X7 e	Fault NC

[1] with series resistor

Option analog signal

Wire	Signal	Analog signal
9	Analog current	4 ... 20 mA
10	Analog current	4 ... 20 mA
11		
12		

Option fire panel interface

Wire	Siemens FDnet	Bosch LSNi
9	FDnet-A (-)	LSN b1 in
10	FDnet (+)	LSN a in
11	FDnet-B (-)	LSN b2 out
12	FDnet (+)	LSN a out

Option pre-alarm

Wire	Auxiliary relay
9	–
10	–
11	Common
12	Normally open

GTE Industrieelektronik GmbH
Helmholtzstr. 21, 38-40 | 41747 Viersen, GERMANY | ☎ +49 2162 3703-0 | support.adicos@gte.de | www.adicos.com

HOTSPOT-Ex – Application

ADICOS topology concept



Application example

HOTSPOT-Ex with purge-air adapter and mounting bracket for monitoring of a conveyor belt chute for dust-explosive bulk material



HOTSPOT mounting bracket with ball joint





GTE Industrieelektronik GmbH
Helmholtzstr. 21, 38-40 | 41747 Viersen, GERMANY | ☎ +49 2162 3703-0 | support.adicos@gte.de | www.adicos.com